TECHNICAL DATA SHEET

# OKHBH-7EXDT

2-ply PU conveyor belt · Dark green matt · 2.0 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | |
|---|---|---|
| TOP COVER | Material | TPU |
| | Surface | Matt |
| | Colour | Dark green |
| CARCASS | Fabric | Polyester (PET) |
| | Number of plies | 2 |
| BOTTOM | Material | Polyester fabric |
| | Surface | Fabric |
| | Colour | White |

## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Total thickness | **2.0** | mm | *0.079* | *in.* |
| Weight | | | **2.2 kg/m²** | |
| Load at 1% elongation | **6.0** | N/mm | *34.3* | *lbs/in.* |
| Temperature — minimum (1) | **–30** | °C | *–22* | *°F* |
| Temperature — maximum (1) | **80** | °C | *176* | *°F* |
| Max. production width | **3000** | mm | *118* | *in.* |
| Coefficient of friction | | | **Drive side on steel 0.15** | |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Minimum pulley / nose bar | **30** | mm | *1.18* | *in.* |
| ■ Back-flex (counter-bending) pulley | **40** | mm | *1.57* | *in.* |





**PU COVER** dark green · matt
**2-PLY POLYESTER** polyester (pet)
**FABRIC DRIVE FACE** fabric · drive side

CROSS-SECTION — NOT TO SCALE

**TOTAL 2.0 MM / IN.**

## 04 PROPERTIES

| | |
|---|---|
| Antistatic | YES |
| Slider bed | YES |
| Roller bed | YES |
| Low noise | YES |

## 05 APPLICATION

Features: Abrasion resistant, Cut resistant, Oil resistant. Typical uses: Packaging belt, Processing belt, Weighing belt. Industries: Distribution centers. Admissible tensile force 15 N/mm.

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.