TECHNICAL DATA SHEET

OKHBMNM-3H

0-ply polyamide power transmission belt · White rough structure · 1.6 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide compound**
	Surface	**Rough structure**
	Colour	**White**
CARCASS	Fabric	**Polyamide compound**
	Number of plies	**0**
BOTTOM	Material	**Polyamide compound**
	Surface	**Rough structure**
	Colour	**White**


02 TECHNICAL SPECIFICATIONS

Total thickness	**1.6**	mm	*0.063*	*in.*
Weight			**1.5 kg/m²**	
Load at 1% elongation	**1.9**	N/mm	*10.8*	*lbs/in.*
Temperature — minimum (1)	**–20**	°C	*–4*	*°F*
Temperature — maximum (1)	**65**	°C	*149*	*°F*
Max. production width	**1140**	mm	*45*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





☐ **POLYAMIDE COVER** white · rough structure
☐ **1-PLY POLYAMIDE** polyamide compound
☐ **POLYAMIDE COVER** white · rough structure · dr

CROSS-SECTION — NOT TO SCALE

TOTAL 1.6 MM / IN.

04 PROPERTIES

Roller bed	**YES**

05 APPLICATION

Features: Adhesive-free joint, Fibre fly accumulation prevention, Longitudinal flexibility. Typical uses: Cross apron. Industries: Yarn processing.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US