TECHNICAL DATA SHEET

OKHBMNT-8P

2-ply polyamide power transmission belt · Light gray fabric · 1.8 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide (PA) fabric**
	Surface	**Fabric**
	Colour	**Light gray**
CARCASS	Fabric	**Polyamide (PA) fabric / Polyamide compound foil**
	Number of plies	**2**
BOTTOM	Material	**Polyamide (PA) fabric**
	Surface	**Fabric**
	Colour	**Light gray**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.8**	mm	*0.071*	*in.*
Weight			**1.7 kg/m²**	
Load at 1% elongation	**4.2**	N/mm	*24.0*	*lbs/in.*
Temperature — minimum (1)	**–20**	°C	*–4*	*°F*
Temperature — maximum (1)	**60**	°C	*140*	*°F*
Max. production width	**1140**	mm	*45*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**25**	mm	*0.98*	*in.*
■ Back-flex (counter-bending) pulley	**25**	mm	*0.98*	*in.*





CROSS-SECTION — NOT TO SCALE — **TOTAL 1.8 MM / IN.**

04 PROPERTIES

Antistatic	**YES**
Slider bed	**YES**
Roller bed	**YES**

05 APPLICATION

Features: Adhesive-free joint, Constant and gentle positive grip, Dimensionally stable, High abrasion resistance, Non-marking.
Typical uses: Folder belt, Machine tape, Paper handling belt.
Industries: Paper manufacturing and processing, Paper printing and finishing.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US