TECHNICAL DATA SHEET


OKHBMVT-03


Nitrile power transmission belt · Green fine structure · 0.95 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**NBR rubber**
	Surface	**Fine structure**
	Colour	**Green**
CARCASS	Fabric	**Polyamide compound**
BOTTOM	Material	**Polyamide compound**
	Surface	**Fine structure**
	Colour	**Black**





CROSS-SECTION — NOT TO SCALE — **TOTAL 0.95 MM / IN.**

02 TECHNICAL SPECIFICATIONS

Total thickness	**0.95**	mm	*0.037*	*in.*
Weight			**0.95 kg/m²**	
Load at 1% elongation	**0.25**	N/mm	*1.4*	*lbs/in.*
Temperature — minimum (1)	**−20**	°C	*−4*	*°F*
Temperature — maximum (1)	**65**	°C	*149*	*°F*
Max. production width	**1140**	mm	*45*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*

04 PROPERTIES

Antistatic	**YES**

05 APPLICATION

Features: Dual use, Elastic, Free of Fibre accumulation, Free of Fibre-Adhesion, Relaxation prevention. Typical uses: Sliver exit, Carding, Cross apron. Industries: Yarn processing.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.