TECHNICAL DATA SHEET

OKHBNAB-20EFWV-A2W1

3-ply PVC food-grade conveyor belt · White matt · 7 mm
Antistatic · FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	PVC
	Surface	Matt
	Colour	White
CARCASS	Fabric	Polyester (PET)
	Number of plies	3
BOTTOM	Material	PVC
	Surface	Matt
	Colour	White


02 TECHNICAL SPECIFICATIONS

Total thickness	7	mm	0.276	in.
Weight			8.5 kg/m²	
Load at 1% elongation	10	N/mm	57.1	lbs/in.
Temperature – minimum (1)	–10	°C	14	°F
Temperature – maximum (1)	80	°C	176	°F
Max. production width	2800	mm	110	in.
Coefficient of friction			Drive side on steel 0.35	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	300	mm	11.81	in.
■ Back-flex (counter-bending) pulley	300	mm	11.81	in.





☐ PVC COVER — white · matt
☐ 3-PLY POLYESTER — polyester (pet)
☐ PVC COVER — white · matt · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 7 MM / IN.

04 PROPERTIES

Antistatic	YES
FDA compliant compound	YES
EU 10/2011	YES
Roller bed	YES
Troughed	YES

05 APPLICATION

Features: Reverse side coated. Typical uses: Food processing/conveying belt, Transfer belt. Industries: Sugar. Admissible tensile force 25 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.