TECHNICAL DATA SHEET

OKHBNAB-3EVDV-11

1-ply PVC food-grade conveyor belt · Dark green super matt finish · 1.30 mm
Antistatic · FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION


TOP COVER	Material	**PVC**
	Surface	**Super matt finish**
	Colour	**Dark green**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**1**
BOTTOM	Material	**PVC**
	Surface	**Matt**
	Colour	**Dark green**


02 TECHNICAL SPECIFICATIONS

Total thickness	**1.30**	mm	*0.051*	*in.*
Weight			**1.6 kg/m²**	
Load at 1% elongation	**4.0**	N/mm	*22.8*	*lbs/in.*
Temperature – minimum [1]	**–10**	°C	*14*	*°F*
Temperature – maximum [1]	**70**	°C	*158*	*°F*
Max. production width	**1500**	mm	*59*	*in.*
Coefficient of friction			**Drive side on steel 0.30**	

03 MINIMUM PULLEY DIAMETER [2]

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





PVC COVER dark green · super matt fini
1-PLY POLYESTER polyester (pet)
PVC COVER dark green · matt · drive si

CROSS-SECTION – NOT TO SCALE

TOTAL 1.30 MM / IN.

04 PROPERTIES

Antistatic	**YES**
FDA compliant compound	**YES**
EU 10/2011	**YES**
Metal detector friendly	**YES**
Roller bed	**YES**
Troughed	**YES**

05 APPLICATION

Features: Reverse side coated. Typical uses: Side skirt, Wave profile. Industries: Farming and harvesting, Fruit, Primary food packaging, Vegetables. Admissible tensile force 9.0 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES [1] Operating the belt at its limit values may reduce service life. [2] Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.