TECHNICAL DATA SHEET

OKHBNAO-18EEAV

3-ply PVC conveyor belt · Anthracite orb (positive hemispherical) structure · 5.1 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION


TOP COVER	Material	**PVC**
	Surface	**Orb (positive hemispherical) structure**
	Colour	**Anthracite**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**3**
BOTTOM	Material	**Polyester fabric**
	Surface	**Fabric**
	Colour	**White**


02 TECHNICAL SPECIFICATIONS

Total thickness	**5.1**	mm	*0.201*	*in.*
Weight			**5.2 kg/m²**	
Load at 1% elongation	**10**	N/mm	*57.1*	*lbs/in.*
Temperature — minimum (1)	**–10**	°C	*14*	*°F*
Temperature — maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**3000**	mm	*118*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**125**	mm	*4.92*	*in.*
■ Back-flex (counter-bending) pulley	**150**	mm	*5.91*	*in.*





CROSS-SECTION — NOT TO SCALE

TOTAL 5.1 MM / IN.

04 PROPERTIES

Antistatic	**YES**
Metal detector friendly	**YES**
Slider bed	**YES**
Roller bed	**YES**

05 APPLICATION

Features: Abrasion resistant, Chemical resistant, High grip surface, Water resistant. Typical uses: Calibrating machines, Engineered stone processing, Grinding machines, Polishing machines. Industries: Marble and stone. Admissible tensile force 25 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.