TECHNICAL DATA SHEET

OKHBNHM-10ELBV-E3

2-ply PVC conveyor belt · Black super matt finish · 2.1 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**PVC**
	Surface	**Super matt finish**
	Colour	**Black**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**2**
BOTTOM	Material	**Polyester fabric**
	Surface	**Impregnated fabric**
	Colour	**Light green**


02 TECHNICAL SPECIFICATIONS

Total thickness	**2.1**	mm	*0.083*	*in.*
Weight			**2.5 kg/m²**	
Load at 1% elongation	**7**	N/mm	*40.0*	*lbs/in.*
Temperature – minimum (1)	**0**	°C	*32*	*°F*
Temperature – maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**3000**	mm	*118*	*in.*
Coefficient of friction			**Drive side on steel 0.10**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





PVC COVER black · super matt finish
2-PLY POLYESTER polyester (pet)
FABRIC DRIVE FACE impregnated fabric · drive s

CROSS-SECTION – NOT TO SCALE

TOTAL 2.1 MM / IN.

04 PROPERTIES

Antistatic	YES
Flame retardant	YES
Metal detector friendly	YES
Slider bed	YES
Roller bed	YES
Low noise	YES

05 APPLICATION

Features: Energy saving. Typical uses: Heavy-load conveyor belts, Sorting belt. Admissible tensile force 18 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.