TECHNICAL DATA SHEET

OKHBNNH-35EVDV

2-ply PVC conveyor belt · Dark green honeycomb structure · 6.0 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION


TOP COVER	Material	**PVC**
	Surface	**Honeycomb structure**
	Colour	**Dark green**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**2**
BOTTOM	Material	**PVC**
	Surface	**Honeycomb structure**
	Colour	**Dark green**


02 TECHNICAL SPECIFICATIONS

Total thickness	**6.0**	mm	*0.236*	*in.*
Weight			**6.6 kg/m²**	
Load at 1% elongation	**18**	N/mm	*102.8*	*lbs/in.*
Temperature – minimum (1)	**–10**	°C	*14*	*°F*
Temperature – maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**2200**	mm	*87*	*in.*
Coefficient of friction			**Drive side on steel 0.30**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**250**	mm	*9.84*	*in.*
■ Back-flex (counter-bending) pulley	**250**	mm	*9.84*	*in.*





PVC COVER
dark green · honeycomb struc

2-PLY POLYESTER
polyester (pet)

PVC COVER
dark green · honeycomb stru

CROSS-SECTION – NOT TO SCALE

TOTAL 6.0 MM / IN.

04 PROPERTIES

Metal detector friendly	YES
Slider bed	YES
Roller bed	YES

05 APPLICATION

Features: Abrasion resistant, High grip surface. Typical uses: Engineered stone processing. Industries: Marble and stone. Admissible tensile force 32 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US