TECHNICAL DATA SHEET

OKHBNVT-305

3-ply PVC conveyor belt · Dark green super matt finish · 4.5 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**PVC**
	Surface	**Super matt finish**
	Colour	**Dark green**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**3**
BOTTOM	Material	**Polyester fabric**
	Surface	**Fabric**
	Colour	**Gray**


02 TECHNICAL SPECIFICATIONS

Total thickness	**4.5**	mm	*0.177*	*in.*
Weight			**5.6 kg/m²**	
Load at 1% elongation	**11**	N/mm	*62.8*	*lbs/in.*
Temperature – minimum (1)	**–10**	°C	*14*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**3000**	mm	*118*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**125**	mm	*4.92*	*in.*
■ Back-flex (counter-bending) pulley	**125**	mm	*4.92*	*in.*





PVC COVER dark green · super matt fini
3-PLY POLYESTER polyester (pet)
FABRIC DRIVE FACE fabric · drive side

CROSS-SECTION – NOT TO SCALE — **TOTAL 4.5 MM / IN.**

04 PROPERTIES

Antistatic	**YES**
Metal detector friendly	**YES**
Slider bed	**YES**
Roller bed	**YES**

05 APPLICATION

Features: Abrasion resistant, Antistatic, Metal detection units suitable. Typical uses: Decline belt, Incline belt, Infeed belt, Inserting belt, Transfer belt. Industries: Distribution centers, Plastics, Solid wood, Wood panel and boards, Wood surfacing.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.