TECHNICAL DATA SHEET

OKHBPM135RCOS-BE15

1-ply rubber modified tpe food-grade conveyor belt · Blue smooth · 3.3 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Rubber modified TPE**
	Surface	**Smooth**
	Colour	**Blue**
CARCASS	Fabric	**Polyester (PET) scrim**
	Number of plies	**1**
BOTTOM	Material	**Polyester fabric**
	Surface	**Impregnated fleece**
	Colour	**Blue**

02 TECHNICAL SPECIFICATIONS

Total thickness	**3.3**	mm	*0.130*	*in.*
Weight			**4.3 kg/m²**	
Load at 1% elongation	**8.9**	N/mm	*50.8*	*lbs/in.*
Temperature – minimum (1)	**–12**	°C	*10*	*°F*
Temperature – maximum (1)	**82**	°C	*180*	*°F*
Max. production width	**1524**	mm	*60*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**51**	mm	*2.01*	*in.*
■ Back-flex (counter-bending) pulley	**79**	mm	*3.11*	*in.*





04 PROPERTIES

FDA compliant compound	YES
Metal detector friendly	YES
Slider bed	YES
Roller bed	YES
Troughed	YES
Power turns	YES
Low noise	YES

05 APPLICATION

Features: Dimensionally stable, Powerturn suitable, Wear resistant. Typical uses: Infeed belt, Powerturn belt, Transfer belt. Industries: Convenience food, Frozen food, Poultry, Ready meals, Red meat, Vegetables.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.