TECHNICAL DATA SHEET

OKHBRPH2-160RTXB-FR

2-ply neoprene conveyor belt · Black rough top · 6.6 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Neoprene**
	Surface	**Rough top**
	Colour	**Black**
CARCASS	Fabric	**Polyester (PET)/Polyamide (PA) fabric**
	Number of plies	**2**
BOTTOM	Material	**Polyester (PET)/Polyamide (PA) fabric**
	Surface	**Impregnated fabric**
	Colour	**Brown**


02 TECHNICAL SPECIFICATIONS

Total thickness	**6.6**	mm	*0.260*	*in.*
Weight			**6.4 kg/m²**	
Load at 1% elongation	**10.0**	N/mm	*57.1*	*lbs/in.*
Temperature — minimum (1)	**–23**	°C	*–9*	*°F*
Temperature — maximum (1)	**82**	°C	*180*	*°F*
Coefficient of friction			**Drive side on steel 0.45**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**102**	mm	*4.02*	*in.*
■ Back-flex (counter-bending) pulley	**114**	mm	*4.49*	*in.*





CROSS-SECTION — NOT TO SCALE — **TOTAL 6.6 MM / IN.**

04 PROPERTIES

Antistatic	**YES**
Slider bed	**YES**
Roller bed	**YES**
Troughed	**YES**
Power turns	**YES**

05 APPLICATION

Features: Dimensionally stable, High grip surface. Typical uses: Decline belt, Incline belt, Infeed belt, Metering/singulation belt. Industries: Airport, Distribution centers, Parcel distribution / Overnight carrier. Admissible tensile force 9.6 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.