TECHNICAL DATA SHEET

OKHBSNB-18E-07-NVT-8054

3-ply PVC conveyor belt · Anthracite sand finish · 3.3 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**PVC**
	Surface	**Sand finish**
	Colour	**Anthracite**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**3**
BOTTOM	Material	**Polyester fabric**
	Surface	**Fabric**
	Colour	**Off-white**





CROSS-SECTION — NOT TO SCALE — **TOTAL 3.3 MM / IN.**

02 TECHNICAL SPECIFICATIONS

Total thickness	**3.3**	mm	*0.130*	*in.*
Weight			**3.9 kg/m²**	
Load at 1% elongation	**14**	N/mm	*79.9*	*lbs/in.*
Temperature — minimum (1)	**–5**	°C	*23*	*°F*
Temperature — maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**3200**	mm	*126*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Back-flex (counter-bending) pulley	**100**	mm	*3.94*	*in.*

04 PROPERTIES

Antistatic	**YES**
Slider bed	**YES**
Roller bed	**YES**
Low noise	**YES**

05 APPLICATION

Features: Damping behavior. Typical uses: Bunker belt, General conveying belt, Line belt, Transfer belt. Industries: Board manufacturing, Distribution centers, Materials Handling, Parcel sorting, Postal/mail sorting.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.