TECHNICAL DATA SHEET

OKHBST100-U-GLOSS

1-ply PU food-grade conveyor belt · White glossy · 0.80 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	TPU
	Surface	Glossy
	Colour	White
CARCASS	Fabric	Polyester (PET)
	Number of plies	1
BOTTOM	Material	Polyester fabric
	Surface	Impregnated fabric
	Colour	White

02 TECHNICAL SPECIFICATIONS

Total thickness	**0.80**	mm	*0.031*	*in.*
Weight			**0.80 kg/m²**	
Load at 1% elongation	**2.0**	N/mm	*11.4*	*lbs/in.*
Temperature — minimum (1)	**–30**	°C	*–22*	*°F*
Temperature — maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**2200**	mm	*87*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**15**	mm	*0.59*	*in.*
■ Back-flex (counter-bending) pulley	**15**	mm	*0.59*	*in.*





☐ **PU COVER** white · glossy
☐ **1-PLY POLYESTER** polyester (pet)
☐ **FABRIC DRIVE FACE** impregnated fabric · drive s

CROSS-SECTION — NOT TO SCALE

TOTAL 0.80 MM / IN.

04 PROPERTIES

FDA compliant compound	YES
EU 10/2011	YES
Metal detector friendly	YES
Slider bed	YES
Roller bed	YES
Troughed	YES
Power turns	YES

05 APPLICATION

Features: Knife-edge (nosebar) suitable, Oil and fat resistant, Powerturn suitable. Typical uses: Food processing/conveying belt, Powerturn belt. Industries: Baked snacks, Biscuit and Crackers, Chocolate, Convenience food. Knife-edge radius 3 mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.