TECHNICAL DATA SHEET

OKHBTF-15H

1-ply polyamide power transmission belt · White fine textile structure · 1.5 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide compound**
	Surface	**Fine textile structure**
	Colour	**White**
CARCASS	Fabric	**Aramid fabric**
	Number of plies	**1**
BOTTOM	Material	**Polyamide compound**
	Surface	**Fine textile structure**
	Colour	**White**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.5**	mm	*0.059*	*in.*
Weight			**1.6 kg/m²**	
Load at 1% elongation	**15**	N/mm	*85.7*	*lbs/in.*
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**65**	°C	*149*	*°F*
Max. production width	**1140**	mm	*45*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





CROSS-SECTION – NOT TO SCALE — **TOTAL 1.5 MM / IN.**

04 PROPERTIES

Antistatic	**YES**

05 APPLICATION

Features: Abrasion resistant, Dimensionally stable, Energy saving, High modulus of elasticity, Longitudinal flexibility, Low initial tension, Simple and fast joining method. Typical uses: Driving belt, Live roller drive belt. Industries: Letter sorting, Paper printing and finishing. Nominal peripheral force 15 N/mm. Double-sided power transmission.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.