TECHNICAL DATA SHEET

OKHBTM120LR-B

1-ply PVC conveyor belt · Black longitudinal groove structure · 3.9 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**PVC**
	Surface	**Longitudinal groove structure**
	Colour	**Black**
CARCASS	Fabric	**Polyester (PET) scrim**
	Number of plies	**1**
BOTTOM	Material	**Polyester fabric (PET) impregnated with polyvinylchloride**
	Surface	**Fabric**
	Colour	**Black**


02 TECHNICAL SPECIFICATIONS

Total thickness	**3.9**	mm	*0.154*	*in.*
Weight			**4.4 kg/m²**	
Load at 1% elongation	**8.2**	N/mm	*46.8*	*lbs/in.*
Temperature – minimum (1)	**–23**	°C	*–9*	*°F*
Temperature – maximum (1)	**91**	°C	*196*	*°F*
Max. production width	**1829**	mm	*72*	*in.*
Coefficient of friction			**Drive side on steel 0.25**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**40**	mm	*1.57*	*in.*
■ Back-flex (counter-bending) pulley	**70**	mm	*2.76*	*in.*





CROSS-SECTION – NOT TO SCALE — **TOTAL 3.9 MM / IN.**

04 PROPERTIES

Flame retardant	**YES**
Slider bed	**YES**
Roller bed	**YES**
Power turns	**YES**
Low noise	**YES**

05 APPLICATION

Features: Excellent tracking, Flexibility, Low noise applications suitable. Typical uses: Acceleration belt, Decline belt, Incline belt, Induction belt, Light package handling, Metering/singulation belt. Industries: Distribution centers. Admissible tensile force 13 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.