TECHNICAL DATA SHEET

OKHBTT247

1-ply PU food-grade conveyor belt · White fine textile structure · 3.0 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**TPU**
	Surface	**Fine textile structure**
	Colour	**White**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**1**
BOTTOM	Material	**TPU**
	Surface	**Fine textile structure**
	Colour	**White**


02 TECHNICAL SPECIFICATIONS

Total thickness	**3.0**	mm	*0.118*	*in.*
Weight			**3.6 kg/m²**	
Load at 1% elongation	**4.0**	N/mm	*22.8*	*lbs/in.*
Temperature – minimum (1)	**–30**	°C	*–22*	*°F*
Temperature – maximum (1)	**60**	°C	*140*	*°F*
Max. production width	**1500**	mm	*59*	*in.*
Coefficient of friction			**Drive side on steel 0.35**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





☐ **PU COVER** white · fine textile structu
☐ **1-PLY POLYESTER** polyester (pet)
☐ **PU COVER** white · fine textile structu

CROSS-SECTION – NOT TO SCALE — **TOTAL 3.0 MM / IN.**

04 PROPERTIES

FDA compliant compound	**YES**
EU 10/2011	**YES**
Metal detector friendly	**YES**
Roller bed	**YES**

05 APPLICATION

Features: Abrasion resistant on both sides, Oil resistant, Reverse side coated. Typical uses: Food processing/conveying belt, Processing belt. Industries: Candy, Convenience food, Dairy (incl. cheese), Frozen food, Primary food packaging, Primary packaging.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.