TECHNICAL DATA SHEET

OKHBUM220SC-B-N2

1-ply polyester conveyor belt · Black impregnated fleece · 5.5 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyester felt**
	Surface	**Impregnated fleece**
	Colour	**Black**
CARCASS	Fabric	**Polyester (PET) scrim**
	Number of plies	**1**
BOTTOM	Material	**Polyester felt**
	Surface	**Impregnated fleece**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Total thickness	**5.5**	mm	*0.217*	*in.*
Weight			**3.4 kg/m²**	
Load at 1% elongation	**3.8**	N/mm	*21.7*	*lbs/in.*
Temperature – minimum (1)	**–12**	°C	*10*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**2200**	mm	*87*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**100**	mm	*3.94*	*in.*
■ Back-flex (counter-bending) pulley	**100**	mm	*3.94*	*in.*





■ POLYESTER COVER black · impregnated fleece ☐ 1-PLY POLYESTER polyester (pet) scrim ■ POLYESTER COVER black · impregnated fleece ·

CROSS-SECTION – NOT TO SCALE

TOTAL 5.5 MM / IN.

04 PROPERTIES

Slider bed	**YES**
Roller bed	**YES**
Power turns	**YES**
Low noise	**YES**

05 APPLICATION

Features: Abrasion resistant on both sides, Adhesive-free joint, Antistatic, Chemical resistant, Cut resistant, Flexibility in all. Typical uses: Powerturn belt, Processing belt, Punching belt, Stamping belt. Industries: Cardboard converting, Cardboard manufacturing, Distribution centers, Plastics, Wood panel and boards, Wood.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.