TECHNICAL DATA SHEET

OKHBUM220SC-B

1-ply polyester conveyor belt · Black buffed finish · 5.4 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	Polyester felt
	Surface	Buffed finish
	Colour	Black
CARCASS	Fabric	Polyester (PET) scrim
	Number of plies	1
BOTTOM	Material	Polyester felt
	Surface	Buffed finish
	Colour	Black

02 TECHNICAL SPECIFICATIONS

Total thickness	**5.4**	mm	*0.213*	*in.*
Weight			**3.2 kg/m²**	
Load at 1% elongation	**4.8**	N/mm	*27.4*	*lbs/in.*
Temperature – minimum [1]	**–12**	°C	*10*	*°F*
Temperature – maximum [1]	**80**	°C	*176*	*°F*
Max. production width	**2007**	mm	*79*	*in.*
Coefficient of friction			**Drive side on steel 0.20**	

03 MINIMUM PULLEY DIAMETER [2]

■ Minimum pulley / nose bar	**102**	mm	*4.02*	*in.*
■ Back-flex (counter-bending) pulley	**102**	mm	*4.02*	*in.*





■ POLYESTER COVER
black · buffed finish

□ 1-PLY POLYESTER
polyester (pet) scrim

■ POLYESTER COVER
black · buffed finish · driv

CROSS-SECTION – NOT TO SCALE

TOTAL 5.4 MM / IN.

04 PROPERTIES

Antistatic	YES

05 APPLICATION

Features: Abrasion resistant on both sides, Adhesive-free joint, Antistatic, Chemical resistant, Cut resistant, Flexibility in all. Typical uses: Powerturn belt, Processing belt, Punching belt, Stamping belt. Industries: Cardboard converting, Cardboard manufacturing, Distribution centers, Plastics, Wood panel and boards, Wood.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES [1] Operating the belt at its limit values may reduce service life. [2] Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US