TECHNICAL DATA SHEET

OKHBUMS130LR-B

1-ply PVC conveyor belt · Black longitudinal groove structure · 4.3 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**PVC**
	Surface	**Longitudinal groove structure**
	Colour	**Black**
CARCASS	Fabric	**Polyester (PET) scrim**
	Number of plies	**1**
BOTTOM	Material	**Nonwoven (fleece)**
	Surface	**Buffed finish**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Total thickness	**4.3**	mm	*0.169*	*in.*
Weight			**3.6 kg/m²**	
Load at 1% elongation	**7**	N/mm	*40.0*	*lbs/in.*
Temperature – minimum (1)	**–12**	°C	*10*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**1829**	mm	*72*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**51**	mm	*2.01*	*in.*
■ Back-flex (counter-bending) pulley	**76**	mm	*2.99*	*in.*





■ **PVC COVER** black · longitudinal groove
□ **1-PLY POLYESTER** polyester (pet) scrim
■ **FELT COVER** black · buffed finish · driv

CROSS-SECTION – NOT TO SCALE

TOTAL 4.3 MM / IN.

04 PROPERTIES

Antistatic	**YES**
Slider bed	**YES**
Roller bed	**YES**
Troughed	**YES**
Power turns	**YES**
Low noise	**YES**

05 APPLICATION

Features: Absorption of shock loads, Antistatic, Constant coefficient of friction, Edges wear resistant, Flat laying, Good lace retention, High coefficient of friction surface, Low noise applications suitable. Typical uses: Acceleration belt, Deceleration belt, Decline belt, Incline belt, Induction belt, Infeed belt, Light package handling. Industries: Airport, Distribution centers.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.