TECHNICAL DATA SHEET

OKHBW1000F-OE

1-ply PU conveyor belt · Orange smooth · 4.4 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**TPU**
	Surface	**Smooth**
	Colour	**Orange**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**1**
BOTTOM	Material	**TPU**
	Surface	**Smooth**
	Colour	**Orange**

02 TECHNICAL SPECIFICATIONS

Total thickness	**4.4**	mm	*0.173*	*in.*
Weight			**3.8 kg/m²**	
Temperature — minimum (1)	**–12**	°C	*10*	*°F*
Temperature — maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**1829**	mm	*72*	*in.*





CROSS-SECTION — NOT TO SCALE

TOTAL 4.4 MM / IN.

03 APPLICATION

Features: Cut resistant, Oil resistant. Typical uses: Oil Containment.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US