TECHNICAL DATA SHEET

OKHBWVT-158

2-ply PU conveyor belt · Transparent silk finish · 1.8 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	TPU
	Surface	Silk finish
	Colour	Transparent
CARCASS	Fabric	Polyester (PET) fabric
	Number of plies	2
BOTTOM	Material	Polyester fabric
	Surface	Impregnated fabric
	Colour	White


02 TECHNICAL SPECIFICATIONS

Total thickness	**1.8**	mm	*0.071*	*in.*
Weight			**2.0 kg/m²**	
Load at 1% elongation	**4.0**	N/mm	*22.8*	*lbs/in.*
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**100**	°C	*212*	*°F*
Max. production width	**2000**	mm	*79*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**40**	mm	*1.57*	*in.*
■ Back-flex (counter-bending) pulley	**60**	mm	*2.36*	*in.*





CROSS-SECTION – NOT TO SCALE — TOTAL 1.8 MM / IN.

04 PROPERTIES

Metal detector friendly	YES
Slider bed	YES
Roller bed	YES

05 APPLICATION

Features: Abrasion resistant, Cut resistant, Oil and fat resistant, Small pulley diameter suitable. Typical uses: Stamping belt. Industries: Automotive components, Various industries. Admissible tensile force 12 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.