TECHNICAL DATA SHEET

# OKHBWVT-236

2-ply PU food-grade conveyor belt · Cobalt blue silk finish · 1.35 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | |
|---|---|---|
| TOP COVER | Material | TPU |
| | Surface | Silk finish |
| | Colour | Cobalt blue |
| CARCASS | Fabric | Polyester (PET) |
| | Number of plies | 2 |
| BOTTOM | Material | Polyester fabric |
| | Surface | Impregnated fabric |
| | Colour | Cobalt blue |


## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Total thickness | **1.35** | mm | *0.053* | *in.* |
| Weight | | | **1.4 kg/m²** | |
| Load at 1% elongation | **4.8** | N/mm | *27.4* | *lbs/in.* |
| Temperature — minimum (1) | **–20** | °C | *–4* | *°F* |
| Temperature — maximum (1) | **100** | °C | *212* | *°F* |
| Max. production width | **2000** | mm | *79* | *in.* |
| Coefficient of friction | | | **Drive side on steel 0.10** | |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Minimum pulley / nose bar | **15** | mm | *0.59* | *in.* |
| ■ Back-flex (counter-bending) pulley | **25** | mm | *0.98* | *in.* |






CROSS-SECTION — NOT TO SCALE — TOTAL 1.35 MM / IN.

## 04 PROPERTIES

| | |
|---|---|
| FDA compliant compound | YES |
| EU 10/2011 | YES |
| Metal detector friendly | YES |
| Slider bed | YES |
| Roller bed | YES |

## 05 APPLICATION

Features: Abrasion resistant, Excellent release, Frayless edges, Oil and fat resistant, Small pulley diameter suitable. Typical uses: Accumulation belt, Diverting belt, Food processing/conveying belt. Industries: Baked snacks, Biscuit and Crackers, Bread, Chocolate, Convenience food, Frozen food, Pasta, Pastry, Pizza. Admissible tensile force 12 N/mm. Knife-edge radius 4 mm.

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.