TECHNICAL DATA SHEET

OKHBXVT-2068

3-ply cross-linked pu power transmission belt · Black impregnated fabric · 0.90 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Cross-linked PU**
	Surface	**Impregnated fabric**
	Colour	**Black**
CARCASS	Fabric	**Polyamide (PA)**
	Number of plies	**3**
BOTTOM	Material	**Cross-linked PU**
	Surface	**Impregnated fabric**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Total thickness	**0.90**	mm	*0.035*	*in.*
Weight			**0.75 kg/m²**	
Load at 1% elongation	**1.6**	N/mm	*9.1*	*lbs/in.*
Temperature — minimum (1)	**–30**	°C	*–22*	*°F*
Temperature — maximum (1)	**100**	°C	*212*	*°F*
Max. production width	**1140**	mm	*45*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**15**	mm	*0.59*	*in.*
■ Back-flex (counter-bending) pulley	**15**	mm	*0.59*	*in.*





FABRIC TOP FACE impregnated fabric · black
3-PLY POLYAMIDE polyamide (pa)
FABRIC DRIVE FACE impregnated fabric · drive s

CROSS-SECTION — NOT TO SCALE — **TOTAL 0.90 MM / IN.**

04 PROPERTIES

Antistatic	**YES**
Slider bed	**YES**

05 APPLICATION

Features: Easy release, Constant and gentle positive grip, High abrasion resistance, Non-marking. Typical uses: Folder belt, Machine tape, Paper handling belt, Processing belt. Industries: Paper manufacturing and processing, Paper printing and finishing. Admissible tensile force 8.0 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.