TECHNICAL DATA SHEET

OKHBXVT-2249

3-ply polyamide conveyor belt · Black impregnated fabric · 3.5 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide**
	Surface	**Impregnated fabric**
	Colour	**Black**
CARCASS	Fabric	**Polyamide (PA)**
	Number of plies	**3**
BOTTOM	Material	**NBR rubber**
	Surface	**Impregnated fabric**
	Colour	**Green (green)**


02 TECHNICAL SPECIFICATIONS

Total thickness	**3.5**	mm	*0.138*	*in.*
Weight			**3.7 kg/m²**	
Temperature — minimum (1)	**–20**	°C	*–4*	*°F*
Temperature — maximum (1)	**100**	°C	*212*	*°F*
Max. production width	**2400**	mm	*94*	*in.*
Coefficient of friction			**Drive side on steel 0.25**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**200**	mm	*7.87*	*in.*





FABRIC TOP FACE — impregnated fabric · black
3-PLY POLYAMIDE — polyamide (pa)
FABRIC DRIVE FACE — impregnated fabric · drive s

CROSS-SECTION — NOT TO SCALE

TOTAL 3.5 MM / IN.

04 PROPERTIES

Slider bed	**YES**
Roller bed	**YES**

05 APPLICATION

Features: Abrasion resistant, Cut resistant. Typical uses: Punching belt. Industries: Automotive components, Leather, Various industries.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.