TECHNICAL DATA SHEET

OKHBXVT-2346

2-ply PU conveyor belt · Black smooth · 1.5 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**TPU**
	Surface	**Smooth**
	Colour	**Black**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**2**
BOTTOM	Material	**Polyester fabric**
	Surface	**Impregnated fabric**
	Colour	**Off-white**


02 TECHNICAL SPECIFICATIONS

Total thickness	**1.5**	mm	*0.059*	*in.*
Weight			**1.7 kg/m²**	
Load at 1% elongation	**6.5**	N/mm	*37.1*	*lbs/in.*
Temperature – minimum (1)	**–30**	°C	*–22*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**4000**	mm	*157*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**20**	mm	*0.79*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





CROSS-SECTION – NOT TO SCALE — **TOTAL 1.5 MM / IN.**

04 PROPERTIES

Antistatic	YES
Slider bed	YES
Roller bed	YES
Low noise	YES

05 APPLICATION

Features: Abrasion resistant, Antistatic, Dimensionally stable, Flat laying, Low noise applications suitable, Small pulley diameter suitable. Typical uses: Transfer belt, Weighing belt. Industries: Distribution centers, General conveying, Letter sorting, Solid wood, Textile others. Admissible tensile force 12 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.