TECHNICAL DATA SHEET

# OKMU1-7004

2-ply urethane conveyor belt · White bare · 1.52 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | |
|---|---|---|
| TOP COVER | Material | **Urethane** |
| | Surface | **Bare** |
| | Colour | **White** |
| CARCASS | Fabric | **Cotton/Polyester** |
| | Number of plies | **2** |
| BOTTOM | Surface | **Bare** |

## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Total thickness | **1.52** | mm | *0.06* | *in.* |
| Weight | | | **0.03 lb/ft²** | |
| Working tension | **80** | PIW | *14.0* | *N/mm* |
| Elongation | | | **Less than 2%** | |
| Temperature — minimum (1) | **–18** | °C | *0* | *°F* |
| Temperature — maximum (1) | **82** | °C | *180* | *°F* |
| Max. stocked width | **1829** | mm | *72* | *in.* |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Minimum pulley / nose bar | **4** | mm | *0.16* | *in.* |
| ■ Back-flex (counter-bending) pulley | **6** | mm | *0.25* | *in.* |





FABRIC TOP FACE
bare · white

2-PLY POLYESTER
cotton/polyester

FABRIC DRIVE FACE
bare · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 1.52 MM / 0.06 IN.

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.