TECHNICAL DATA SHEET

OKMU1-9230

Urethane conveyor belt · Blue smooth (dull finish) · 11.05 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Urethane**
	Surface	**Smooth (Dull Finish)**
	Colour	**Blue**
	Hardness	**98 Shore A**
CARCASS	Fabric	**N/A**
BOTTOM	Surface	**Smooth (Dull Finish)**

02 TECHNICAL SPECIFICATIONS

Total thickness	**11.05** mm	*0.435 in.*
Weight		**0.0867 lb/ft²**
Max. stocked width	**1524** mm	*60 in.*





URETHANE COVER blue · smooth (dull finish) | **1-PLY N/A** n/a | **BOTTOM COVER** smooth (dull finish) · drive

CROSS-SECTION — NOT TO SCALE

TOTAL 11.05 MM / 0.435 IN.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.