TECHNICAL DATA SHEET

# OKMU2-2125

1-ply PVC conveyor belt · White hemp impression rough top · 7.87 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | |
|---|---|---|
| TOP COVER | Material | **PVC** |
| | Surface | **Hemp Impression Rough Top** |
| | Colour | **White** |
| CARCASS | Fabric | **Interwoven Polyester** |
| | Number of plies | **1** |
| BOTTOM | Surface | **Friction Surface** |


## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Total thickness | **7.87** | mm | *0.31* | *in.* |
| Weight | | | **0.1 lb/ft²** | |
| Working tension | **100** | PIW | *17.5* | *N/mm* |
| Elongation | | | **Less than 2%** | |
| Temperature — minimum (1) | **–18** | °C | *0* | *°F* |
| Temperature — maximum (1) | **82** | °C | *180* | *°F* |
| Max. stocked width | **1829** | mm | *72* | *in.* |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Minimum pulley / nose bar | **76** | mm | *3* | *in.* |
| ■ Back-flex (counter-bending) pulley | **114** | mm | *4.5* | *in.* |





□ **PVC COVER** white · hemp impression roug
□ **1-PLY POLYESTER** interwoven polyester
□ **FABRIC DRIVE FACE** friction surface · drive sid

CROSS-SECTION — NOT TO SCALE

**TOTAL 7.87 MM / 0.31 IN.**

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.