TECHNICAL DATA SHEET

OKMU4-6001

1-ply nitrile conveyor belt · Orange sand grit · 1.90 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS


01 CONSTRUCTION

TOP COVER	Material	**NBR**
	Surface	**Sand Grit**
	Colour	**Orange**
CARCASS	Fabric	**Cotton/Polyester**
	Number of plies	**1**
BOTTOM	Surface	**Friction Surface**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.90**	mm	*0.075*	*in.*
Weight			**0.031 lb/ft²**	
Temperature — minimum (1)	**–18**	°C	*0*	*°F*
Temperature — maximum (1)	**121**	°C	*250*	*°F*





NITRILE COVER — orange · sand grit
1-PLY POLYESTER — cotton/polyester
FABRIC DRIVE FACE — friction surface · drive sid

CROSS-SECTION — NOT TO SCALE

TOTAL 1.90 MM / 0.075 IN.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.