TECHNICAL DATA SHEET

OKMU5-3734-SOR

3-ply sor conveyor belt · Black smooth cover · 10.41 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material		**SOR**
	Thickness	**4.76** mm	*0.187 in.*
	Surface		**Smooth Cover**
	Colour		**Black**
	Hardness		**65 Shore A**
CARCASS	Fabric		**Polyester/Nylon**
	Number of plies		**3**
BOTTOM	Surface		**Smooth Cover**





SOR COVER black · smooth cover
3-PLY POLYESTER polyester/nylon
BOTTOM COVER smooth cover · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 10.41 MM / 0.41 IN.

02 TECHNICAL SPECIFICATIONS

Total thickness	**10.41** mm	*0.41 in.*
Weight		**0.217 lb/ft²**
Working tension	**330** PIW	*57.7 N/mm*
Elongation		**Less than 4%**
Temperature — minimum (1)	**−29** °C	*−20 °F*
Temperature — maximum (1)	**177** °C	*350 °F*
Max. stocked width	**1829** mm	*72 in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**305** mm	*12 in.*

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.