TECHNICAL DATA SHEET

# OKMU6-7001

2-ply nitrile conveyor belt · Green rough texture · 0.79 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | |
|---|---|---|
| TOP COVER | Material | **NBR** |
| | Surface | **Rough Texture** |
| | Colour | **Green** |
| CARCASS | Fabric | **Polyamide** |
| | Number of plies | **2** |
| BOTTOM | Surface | **Bare** |






CROSS-SECTION — NOT TO SCALE — **TOTAL 0.79 MM / 0.031 IN.**

## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Total thickness | **0.79** | mm | *0.031* | *in.* |
| Weight | | | **0.015 lb/ft²** | |
| Working tension | **28** | PIW | *4.9* | *N/mm* |
| Elongation | | | **Less than 1%** | |
| Temperature — minimum (1) | **−20** | °C | *−4* | *°F* |
| Temperature — maximum (1) | **80** | °C | *176* | *°F* |
| Coefficient of friction | | | **0.4** | |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Minimum pulley / nose bar | **15** | mm | *0.59* | *in.* |
| ■ Back-flex (counter-bending) pulley | **25** | mm | *1* | *in.* |

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.