TECHNICAL DATA SHEET

OKMU6-7110

1-ply nitrile conveyor belt · Green adhesive · 1.52 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	NBR
	Surface	Adhesive
	Colour	Green
CARCASS	Fabric	N/A
	Number of plies	1
BOTTOM	Surface	Bare





NITRILE COVER — green · adhesive
1-PLY N/A — n/a
FABRIC DRIVE FACE — bare · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 1.52 MM / 0.06 IN.

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.52**	mm	*0.06*	*in.*
Weight			**0.024 lb/ft²**	
Working tension	**5**	PIW	*0.9*	*N/mm*
Elongation			**Less than 1%**	
Temperature — minimum [1]	**−20**	°C	*−4*	*°F*
Temperature — maximum [1]	**60**	°C	*140*	*°F*

03 MINIMUM PULLEY DIAMETER [2]

■ Minimum pulley / nose bar	**15**	mm	*0.6*	*in.*
■ Back-flex (counter-bending) pulley	**25**	mm	*1*	*in.*

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES [1] Operating the belt at its limit values may reduce service life. [2] Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.