TECHNICAL DATA SHEET

OKMU7-2916

Neoprene conveyor belt · Black smooth · 19.05 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Neoprene**
	Surface	**Smooth**
	Colour	**Black**
	Hardness	**60 Shore A**
BOTTOM	Surface	**Smooth**

02 TECHNICAL SPECIFICATIONS

Total thickness	**19.05**	mm	*0.75*	*in.*
Weight			**0.288 lb/ft²**	
Elongation			**350%**	
Temperature — minimum [1]	**−68**	°C	*−90*	*°F*
Temperature — maximum [1]	**71**	°C	*160*	*°F*
Max. stocked width	**1219**	mm	*48*	*in.*





NEOPRENE — ONE LAYER
black · smooth

CROSS-SECTION — NOT TO SCALE

TOTAL 19.05 MM / 0.75 IN.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES [1] Operating the belt at its limit values may reduce service life. [2] Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.