TECHNICAL DATA SHEET

OKRB-D


PU application belt (built to order)·

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Rubber or polyurethane to suit**





PU — ONE LAYER
homogeneous, no fabric

CROSS-SECTION — NOT TO SCALE

03 APPLICATION

Proudly supplies the meat, poultry, and fish industries with premium Deboning Belts. Our Deboning Belts are used by the industry's leading machine manufacturers, such as Baader, SepaMatic, Bibun, Toyo, and Provisur machines. Serving the Food Processing Industry for over 50 years: Truly endless, with no seam or splice Rubber and Urethane compounds designed specifically for mechanical deboning Fabric construction to allow for flat running and even product distribution

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.