TECHNICAL DATA SHEET

OKRB-RCC


PU application belt (built to order)·

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Rubber or polyurethane to suit**





PU — ONE LAYER
homogeneous, no fabric

CROSS-SECTION — NOT TO SCALE

03 APPLICATION

This roller chain features permanently vulcanized elastomer profiles bonded directly to the chain links, providing reliable grip, cushioning, and noise reduction during operation. Designed for conveying, indexing, and power transmission applications, the elastomer inserts help protect transported products, reduce vibration, and improve traction without sacrificing chain strength. Available in a wide range of standard chain sizes and elastomer profile configurations, this chain is ide

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.