TECHNICAL DATA SHEET

OKRB-S


PU application belt (built to order)·

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Rubber or polyurethane to suit**





PU — ONE LAYER
homogeneous, no fabric

CROSS-SECTION — NOT TO SCALE

03 APPLICATION

Vapor vacuum sealing and capping machines are some of the harshest aspects of a bottling plant. The high heat and steam create issues that can cause production challenges in an otherwise smooth-running operation. has successfully eliminated the belting issues in this application. With years of in-plant experience, we specialize in endless belt technology and high-wear applications. Backing tear out and breaking can be the harshest environme

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.