TECHNICAL DATA SHEET

OKRB-UCL


PU application belt (built to order)·

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Rubber or polyurethane to suit**





PU — ONE LAYER
homogeneous, no fabric

CROSS-SECTION — NOT TO SCALE

03 APPLICATION

, Inc. has developed a revolutionary Capstan Liner made of elastic urethane that offers greater wear and abrasion resistance. This highly elastic liner is easy to install and provides better control, higher speeds, and longer life. Key Features: No Splice, No Seam: By removing the splice area, we eliminate the risk of splice failure. Enhanced Performance: Our advanced urethane liners ensure better control and higher speeds. Longer Lifespan: Enjo

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.