TECHNICAL DATA SHEET

OKUB100720

2-ply polyester food-grade conveyor belt · Transparent pu impregnated · 1.00 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyester Fabric**
	Surface	**PU Impregnated**
	Colour	**Transparent**
	Hardness	**0 Shore A**
CARCASS	Fabric	**Polyester Fabric**
	Number of plies	**2**
BOTTOM	Material	**Polyester Fabric**
	Surface	**PU Impregnated**
	Colour	**Transparent**


02 TECHNICAL SPECIFICATIONS

Total thickness	**1.00**	mm	*0.039*	*in.*
Weight	**1.00 kg/m² 0.2 lb/ft²**			
Load at 1% elongation	**4**	N/mm	*22.8*	*lbs/in.*
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**100**	°C	*212*	*°F*
Max. production width	**3200**	mm	*126*	*in.*
Coefficient of friction	**0.25**			

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**6.00**	mm	*0.24*	*in.*
■ Back-flex (counter-bending) pulley	**15.00**	mm	*0.59*	*in.*





CROSS-SECTION – NOT TO SCALE

TOTAL 1.00 MM / 0.039 IN.

04 PROPERTIES

FDA compliant compound	**YES**
USDA meat & poultry	**NO**
USDA dairy	**NO**
Flame retardant	**NO**
Cross rigid	**YES**

05 APPLICATION

Excellent for low force accumulation, dough handling, tire production and a variety of general conveyance needs.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.