TECHNICAL DATA SHEET

OKUB110310

2-ply polyester food-grade conveyor belt · White pu impregnated · 1.30 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Spun Polyester Fabric**
	Surface	**PU Impregnated**
	Colour	**White**
	Hardness	**0 Shore A**
CARCASS	Fabric	**Spun Polyester Fabric**
	Number of plies	**2**
BOTTOM	Material	**Spun Polyester Fabric**
	Surface	**PU Impregnated**
	Colour	**White**


02 TECHNICAL SPECIFICATIONS

Total thickness	**1.30**	mm	*0.051*	*in.*
Weight	**1.20 kg/m² 0.25 lb/ft²**			
Load at 1% elongation	**6**	N/mm	*34.3*	*lbs/in.*
Temperature – minimum (1)	**–30**	°C	*–22*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**3169**	mm	*125*	*in.*
Coefficient of friction	**0.25**			

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**10.00**	mm	*0.39*	*in.*
■ Back-flex (counter-bending) pulley	**10.00**	mm	*0.39*	*in.*





FABRIC TOP FACE — pu impregnated · white
2-PLY POLYESTER — spun polyester fabric
FABRIC DRIVE FACE — pu impregnated · drive side

CROSS-SECTION – NOT TO SCALE — **TOTAL 1.30 MM / 0.051 IN.**

04 PROPERTIES

FDA compliant compound	**YES**
USDA meat & poultry	NO
USDA dairy	NO
Flame retardant	NO
Cross rigid	NO

05 APPLICATION

Impregnated fabric top and bottom

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.