TECHNICAL DATA SHEET

OKUB120240


2-ply pu food-grade conveyor belt · Blue matt · 1.80 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	PU
	Surface	Matt
	Colour	Blue
	Hardness	92 Shore A
CARCASS	Fabric	Polyester Fabric
	Number of plies	2
BOTTOM	Material	PU
	Surface	Rice Grain
	Colour	Blue





PU COVER
blue · matt

2-PLY POLYESTER
polyester fabric

PU COVER
blue · rice grain · drive si

CROSS-SECTION — NOT TO SCALE

TOTAL 1.80 MM / 0.071 IN.

02 TECHNICAL SPECIFICATIONS

Total thickness	1.80	mm	0.071	in.
Weight	2.00 kg/m² 0.41 lb/ft²			
Load at 1% elongation	11	N/mm	62.8	lbs/in.
Temperature — minimum (1)	−40	°C	−40	°F
Temperature — maximum (1)	90	°C	194	°F
Max. production width	2000	mm	79	in.
Coefficient of friction	0.50			

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	25.00	mm	0.98	in.
■ Back-flex (counter-bending) pulley	45.00	mm	1.77	in.

04 PROPERTIES

FDA compliant compound	YES
USDA meat & poultry	NO
USDA dairy	NO
Flame retardant	NO
Cross rigid	YES

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.