TECHNICAL DATA SHEET

OKUB140300

1-ply polyester food-grade conveyor belt · Beige bare · 1.25 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	Polyester/Cotton
	Surface	Bare
	Colour	Beige
	Hardness	0 Shore A
CARCASS	Fabric	Polyester Cotton
	Number of plies	1
BOTTOM	Material	Polyester/Cotton
	Surface	PU Impregnated
	Colour	White

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.25**	mm	*0.049*	*in.*
Weight	**0.60 kg/m² 0.12 lb/ft²**			
Load at 1% elongation	**2**	N/mm	*11.4*	*lbs/in.*
Temperature — minimum (1)	**–30**	°C	*–22*	*°F*
Temperature — maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**2870**	mm	*113*	*in.*
Coefficient of friction	**0.25**			

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**6.00**	mm	*0.24*	*in.*
■ Back-flex (counter-bending) pulley	**30.00**	mm	*1.18*	*in.*





FABRIC TOP FACE
bare · beige

1-PLY POLYESTER
polyester cotton

FABRIC DRIVE FACE
pu impregnated · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 1.25 MM / 0.049 IN.

04 PROPERTIES

FDA compliant compound	YES
USDA meat & poultry	NO
USDA dairy	NO
Flame retardant	NO
Cross rigid	NO

05 APPLICATION

Bottom Side. Rotary Molder Belt

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.