TECHNICAL DATA SHEET

# OKUB351135

1-ply highly abrasion resistant rubber conveyor belt · Black

ORIONTEK
ENGINEERING GOOD SOLUTIONS


## 01 CONSTRUCTION

| | | |
|---|---|---|
| TOP COVER | Material | **Highly Abrasion Resistant Rubber** |
| | Colour | **Black** |
| CARCASS | Fabric | **Nylon** |
| | Number of plies | **1** |
| BOTTOM | Material | **Highly Abrasion Resistant Rubber** |

## 02 TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Weight | **2.20 kg/m² 0.45 lbf/ft²** |






CROSS-SECTION — NOT TO SCALE

## 03 PROPERTIES

| | |
|---|---|
| FDA compliant compound | NO |
| USDA meat & poultry | NO |
| USDA dairy | NO |
| Flame retardant | NO |
| Cross rigid | YES |

## 04 APPLICATION

K2000 Adhesive on Polyamide Surface AF Adhesive for elastomer G (Rubber) Suitable for power transmission and spindle drives (black side = spindle Storage at normal temperature conditions of 20°C/50%

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.