TECHNICAL DATA SHEET

OKWM-CW

Conventional (spiral) weave belt · built to order

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

Single-direction spirals joined by straight rods; runs on straight-faced terminal pulleys

Materials: 304, 316L, 430 stainless; high-carbon and galvanized steel

02 TECHNICAL RANGE

Mesh	**Open to close, to suit product**
Temperature	**To 1,000 °F**

To quote, send width, length, mesh or pitch (spirals and rods per foot), wire gauges, edge type, drive and a photo or sample piece.



03 APPLICATIONS

Washers, dryers, heat treating, light conveying

Oriontek service: new belts, repair sections and splice links; flights, side guards, edge chains and matching sprockets; onsite installation.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Belts are built to order; confirm width, length, splice and guide with Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US