TECHNICAL DATA SHEET

OKYLP22-37HDA

2-ply fabric conveyor belt · Black
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Fabric**
	Colour	**Black**
CARCASS	Fabric	**Polyester, Rigid, Low Noise**
	Number of plies	**2**





FABRIC TOP FACE
fabric · black

2-PLY POLYESTER
polyester, rigid, low noise

FABRIC DRIVE FACE
fabric · drive side

CROSS-SECTION — NOT TO SCALE

03 PROPERTIES

Antistatic	YES

04 APPLICATION

Low running noise.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.