TECHNICAL DATA SHEET

OT-FDA-T10-KNOBS

Polyurethane timing belt · T10 · food grade

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

BELT	Profile / pitch	**T10**
	Material	**Thermoplastic polyurethane**
	Hardness	**84 ° Shore A**
	Colour	**Blue en transparent**
	Backing / coating	**Knobs profile**
CORDS	Standard cords	**Kevlar 0,6mm**

02 TECHNICAL SPECIFICATIONS

Width tolerance	**+/- 0,5mm**
Standard widths (mm)	**Up to 150mm**
Operating temperature ⁽¹⁾	**10 degC to 50 degC**



03 PULLEYS (2)

■ Minimum pulley diameter	**65** mm	*2.56* *in.*

04 FEATURES

FDA / food contact compound

Oriontek service: supplied open length, endless-joined or truly endless; machined to customer drawing with welded cleats, profiles, tracking guides, backings and drilled holes. Matching timing pulleys and clamping plates available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Pulley minimums depend on the cord type and belt tension specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.