TECHNICAL DATA SHEET

OT-T10-440

Polyurethane timing belt · T10

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

BELT	Profile / pitch	T10
	Material	PU
	Hardness	92 ° Shore A
CORDS	Standard cords	0.6 mm

02 TECHNICAL SPECIFICATIONS

Width tolerance	+/- 0.5 mm
Height tolerance	+/- 0.3 mm
Length tolerance	+/- 0.8 mm/m
Weight	+/- 48g/10mm belt width per meter
Standard widths (mm)	16, 20, 25, 32, 50 & 100 mm
Delivery	440 mm



03 PULLEYS [2]

Minimum number of pulley teeth				12 teeth
■ Minimum pulley diameter	36.35	mm	*1.43*	*in.*
■ Minimum counter-bending diameter	60.00	mm	*2.36*	*in.*

Oriontek service: supplied open length, endless-joined or truly endless; machined to customer drawing with welded cleats, profiles, tracking guides, backings and drilled holes. Matching timing pulleys and clamping plates available.

NOTES [1] Operating the belt at its limit values may reduce service life. [2] Pulley minimums depend on the cord type and belt tension specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.