TECHNICAL DATA SHEET

OT-T25-TRULY-ENDLESS

Polyurethane timing belt · T2,5 · 5 - truly endless

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

BELT	Profile / pitch	
	Version	
	Material	
	Hardness	
	Colour	
CORDS	Standard cords	

02 TECHNICAL SPECIFICATIONS

Width tolerance	
Height tolerance	
Length tolerance	
Weight	
Standard widths (mm)	
Delivery	**120 mm, 145 mm, 160 mm, 177,5 mm, 180 mm, 182,5 mm, 200 mm, 210 mm, 230 mm, 245 mm, 265 mm, 277,5 mm, 285 mm, 290 mm, 305 mm, 317**

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Pulley minimums depend on the cord type and belt tension specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US